

**Features:**

- **100% Compatible** - Won't void OEM warranty
- **Operate full-shift** - 2X the capacity of OEM alternatives
- **Save money** - Purchase fewer batteries over time as a result of increased cycle life
- **Extreme performance** - Widest temperature tolerance available

**Cell Specifications**

Chemistry:	NEOCELL <sup>®</sup> LiP
Voltage:	7.4 VDC
Capacity:	2850 mAh
Operating Temp.:	-20°C to 60°C (-4°F to 140°F)

**Battery Dimensions**

Length:	18.5 mm
Width:	55.5 mm
Height:	129 mm
Weight:	147 g

**About Us**

Global Technology Systems, Inc. ("GTS") is the trusted expert in mobile power technology. GTS designs and manufactures high-performance batteries, chargers, and power management technologies for essential mobile devices. Millions of public safety, government, military, and business professionals rely on GTS to power mission critical communications and mobile computing applications. Founded in 2000, GTS is headquartered in Framingham, Massachusetts.

Maximize the Performance of your MOTOTRBO™ XPR6500, XPR6550, XPR6580, XPR6300, XPR6350 & XPR6380 two-way radios.

The H4077-LiP is replacement battery for the OEM P/N PMNN4066, PMNN4069 & PMNN4077 batteries used in MOTOTRBO two-way radios.

**The NEOCELL<sup>®</sup> Advantage**

NEOCELL is a lightweight, high performance alternative to traditional battery chemistries. With longer runtimes, higher capacities, and extended life, NEOCELL is the ultimate solution for improved performance.



Each battery is guaranteed to be free from defects in materials and workmanship and can maintain a minimum of 80% of its rated capacity for 24 months from date of shipment under normal use.

**For Pricing or Additional Information Contact:**

**Global Technology Systems, Inc.**  
550 Cochituate Road Framingham, MA 01701  
US: 1.800.267.2711 ■ EU: 00800.5390.5390  
[www.GTSpower.com](http://www.GTSpower.com)  @GTSpower1