

# HCH-3006-CHG

## Six-Bay MC3000 Battery Charger

### Charger Specifications:

#### Temperature Limits:

Operating Range: 0°C to +35°C  
Storage Range: -40°C to +85°C

#### Dimensions:

Width: 6.25 inches (159 mm)  
Length: 6.5 inches (165 mm)  
Height: 2.6 inches (66 mm) - without  
batteries or devices inserted.  
Weight: 1.2 pounds (0.54 kg)

#### Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 24 months from date of



### Compatible Batteries:

#### HMC3000-IMG-Li Honeywell® Battery

- Highest quality cells used.
- Longer cycle life.
- Extremely rugged.
- Rigorous testing.



Trademarks are the sole property of their respective owners.  
The Honeywell® Trademark is used under license from Honeywell® International Inc.

12.01.24



#### Dual-chemistry charger

Supports Li-Ion and Li-Polymer chemistries.

#### Hassle-free mounting

Utilizes same mounting bracket as Symbol® chargers for easy wall mounting.

Made of highly rugged aerospace grade aluminium housing.

Includes power supplies and cable.

#### More efficiency in less space

Charges 50% more batteries in same space as OEM chargers.

#### Tri-color charging indications

A charging LED indicates charging

