

# HCH-3030-CHG

## Charger Specifications:

### Temperature Limits:

Operating Range: 0°C to 40°C  
32°F to 104°F

Storage Range: -10°C to 50°C  
14°F to 122°F

### Dimensions:

Length: 333 mm  
Width: 159.69 mm  
Height: 113 mm  
without device inserted.  
Weight: 900 g

### Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 24 months from date of shipment under normal use.



## Compatible Batteries

HMC3X00-Li(S) GTS Battery  
HMC3000-LAS-Li GTS Battery

- Highest quality cells used
- Longer cycle life
- Extremely rugged
- Rigorous testing



Trademarks are the sole property of their respective owners.

14.05.16

## 3 Bay Cradle Charger for the Motorola® MC3000/MC3100 Devices

**More charging in less space**  
Charges 50% more batteries in same space as OEM charger.

Includes power supplies and cable.

**Dual-chemistry charger**  
Supports Li-Ion and Li-Polymer chemistries.

**Tri-color charging indications**  
A charging LED indicates charging status.



**Hassle-free mounting**  
Utilizes same mounting bracket as Symbol® chargers for easy wall mounting.

Made of highly rugged aerospace grade aluminum housing.

For Pricing or Additional Information Contact:

Global Technology Systems, Inc.  
550 Cochituate Road Framingham, MA 01701  
US: 1.800.267.2711 ■ EU: 00800.5390.5390  
[www.GTSpower.com](http://www.GTSpower.com) @GTSpower1

