

HCH-P7301-DCC-CHG

Features:

- One hand lock and release
- Built to meet 50G crash test criteria
- Small surveillance style charger

Charger Specifications:

Temperature Limits:

Operating Range: 0°C to +45°C

32°F to +113°F

Storage Range: -20.0°C to +60°C

-4°F to +140°F

Dimensions:

Length: 67.9 mm (2.67 in)

Width: 56.0 mm (2.20 in)

Height: 100.8 mm (3.96 in)

Weight: 450.0 g (1 lb)

Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 24 months from date of shipment under normal use.



Compatible Batteries:

HNPA9-LiP NEOCELL® Battery



Trademarks are the sole property of their respective owners.

14.03.28

Maximize the performance of your Harris P7300 and XG75 series radios with our DC in-vehicle charger.



Supports NiMH, Li-Ion, and Li-Poly chemistries.

Includes power supplies and cable.

Made of highly rugged aerospace grade aluminum housing.

More efficiency in less space.

Hassle- free wall mounting.

For Pricing or Additional Information Contact:

Global Technology Systems, Inc.
550 Cochituate Road Framingham, MA 01701
US: 1.800.267.2711 ■ EU: 00800.5390.5390
www.GTSpower.com @GTSpower1

