

**Features**

- Independent 3<sup>rd</sup> party NRTL certified battery.
- Contains the highest quality battery cells.
- Provides excellent discharge characteristics.
- Extends operating time and reduces total number of batteries needed.
- Rigorous testing including temperature, vibration, shock, drop, short circuit, and overcharge.

**Cell Specifications**

Cell Manufacturer:	Sanyo
Chemistry:	Lithium Ion
Voltage:	7.4 VDC
Capacity:	2500 mAh
Cell:	UF653450

**Battery Dimensions**


Length:	114.5 mm	[4.5 in]
Width:	61.9 mm	[2.4 in]
Height:	26.2 mm	[1.0 in]
Weight:	161.0 g	[0.4 lb]

**About Us**

Global Technology Systems, Inc. (“GTS”) is the trusted expert in mobile power technology. GTS designs and manufactures high-performance batteries, chargers and power management technologies for essential mobile devices. Millions of public safety, government, military and business professionals rely on GTS to power mission critical communications and mobile computing applications.

Intrinsically safe battery for  
**XG75/P7300/P5300** series radios  
 Replaces OEM BT-023406-006 battery.  
 Class I, II, III, Division 1, Group C-G, T3C Ta = 60°  
 Class I, II, III, Division 2, Groups A-G, T4 Ta = 60°





Each battery is guaranteed to be free from defects in materials and workmanship and can maintain a minimum of 80% of its rated capacity for 12 months from date of shipment under normal use.