

Features:

- Contains the highest quality battery cells.
- Provides excellent discharge characteristics.
- Provides longer cycle life.
- Extends operating time and reduces the total number of batteries needed.
- Rigorous testing including temperature, vibration, shock, drop, short circuit and overcharge.

Cell Specifications

Cell Manufacturer:	Sanyo
Chemistry:	Lithium Ion
Voltage:	7.4 Volts
Capacity:	1800 mAh

Battery Dimensions

Length:	85.0 mm
Width:	44.7 mm
Height:	28.1 mm
Weight:	120 g

Maximize the Performance of your Symbol® PDT7500.

Replaces the OEM BTRY-21-38602-06, 21-65782-06 battery.



Each battery is guaranteed to be free from defects in materials and workmanship and can maintain a minimum of 80% of its rated capacity for 12 months from date of shipment under normal use.

Note

The Symbol® battery P/N 21-65782-06 contained a proprietary Dallas Microprocessor (DS2438 modified series) which allowed the Symbol® battery to display advanced Windows CE or Custom battery monitoring data. The Honeywell® Batteries HS7500-Li battery is not designed to accommodate these advanced Windows CE or Custom applications, but will provide the necessary voltage and capacity to run these devices efficiently.

The HS7500-Li is compatible with basic Windows CE and Symbol® basic battery monitoring applications.

About Us

Global Technology Systems, Inc. ("GTS") is the trusted expert in mobile power technology. GTS designs and manufactures high-performance batteries, chargers, and power management technologies for essential mobile devices. Millions of public safety, government, military, and business professionals rely on GTS to power mission critical communications and mobile computing applications. Founded in 2000, GTS is headquartered in Framingham, Massachusetts.

For Pricing or Additional Information Contact:

Global Technology Systems, Inc.
550 Cochituate Road Framingham, MA 01701
US: 1.800.267.2711 ■ EU: 00800.5390.5390
www.GTSpower.com  @GTSpower1